Quadrifoglio Group



www.quadrifoglio.com



Specification sheet SEVEN

MELAMINE TOPS

18mm easy to clean scratch-resistant anti-reflective melamine faced chipboard (MFC) floating top. 10mm high chamfered edges finished with 1mm impact resistant matching Abs. Both ends feature 10mm high 5mm thick polished aluminium trims recessed into the desk surface. Panel density: 670/730 kgs per cubic meter

Finish options:



LACQUERED MELAMINE TOPS

18mm scratch & abrasion resistant lacquered melamine faced chipboard (MFC) floating top. 10mm high chamfered edges finished with 1mm impact resistant matching Abs. Matt lacquers. Both ends feature 10mm high 5mm thick polished aluminium trims recessed into the desk surface. Panel density: 670/730 kgs per cubic meter

Finish options:



Production lead time: 5 weeks excluding delivery time. Apart from the shown finish options any RAL color can be made to order.

GLASS TOPS

10mm fingerprint-proof back painted tempered glass with a satin white finish. Floating top supported on stainless steel spacers. Polished edges and radius corners.


Finish options:



PORCELAIN TOP

18mm melamine faced chipboard (MFC) top bonded to a 3 or 5mm PORCELAIN top with 1.5mm 45° beveled flat edges; the top is either 5mm or 3mm thick depending on the finish.

Finish options:



FRAMES

Goalpost and Loop leg frame. Manufactured from epoxy powder coated or chromed steel.

Finish options:

















Legs made from 94×30mm pentagon-shaped 2mm steel tube.



Beams made from 100×40mm rectangular 1.5mm epoxy powder coated steel tube.



Goalpost leg frame: 0-15mm adjustable levelling feet made of polyethylene, 18mm diameter.



Loop leg frame: 0-13mm adjustable levelling feet made of polyethylene, 35mm diameter. Layout

180-200-220	_
	100



MATERIALS AND RECYCLABILITY

MFC panels used for SEVEN range tables are solely manufactured with 100% recycled wood and fully meet requisites of formaldeyde low emissions (CARB Quality Award CATAS Certificate). Rasins used for panels and melamines are free of SVHC substances (to be found in the ECHA list updated as of 12/01/2017).



STANDARDS

SEVEN range has passed the following tests, attested by Alba analysis laboratory in San Giovanni al Natisone (UD).

- · Tables and desks dimensions EN 527-1:2011
- Safety mechanical requirements EN 527-2:2002, par. 3
- Horizontal static load test EN 527-3:2003, par. 5.3
- Vertical static load test EN 527-3:2003, par. 5.2
- Horizontal fatigue test EN 527-3:2003, par. 5.4
- Vertical fatigue test EN 527-3:2003, par. 5.4
- Stability EN 527-3:2003, par. 5.1
- Drop test EN 527-3:2003, par. 5.6
- Worktops bend UNI 8594:2004
- Legs impact UNI 9086:1987



CERTIFICATES

Constantly receptive to market requirements, Quadrifoglio Sistemi d'Arredo pay special attention on quality and safety contents in order to provide high products and services. The Company has reached certifications UNI EN ISO 9001/2015, UNI EN ISO 14001/2015 and UNI EN ISO 45001/2018 to confirm his policy. Our products are certified and ensured by FSC™ and ECOLOGICAL PANEL.









GREEN ENERGY

The Company had installed the photovoltaic system with 4.500 solar panels in a 7.350 m² surface that covers almost entirely the factory. The photovoltaic is able to produce 1Mw of a quiet green energy, that does not harm the environment and is waste-free. With his high production capacity the photovoltaic allows us to reduce emissions in the atmosphere of all those polluting substances and to those that contribute to the greenhouse effects. Consequently, such measures make us save every year 180 tonne of petrol oil, 440 tonne of CO2, 514kg of sulphur dioxide, 448 kg of nitrogen oxide and 23kg of dust.



TRANSPORT

Packaging is reduced in order to decrease volumes. Goods collections are responsibily managed and organised with the aim of optimise transports, reducing atmosphere emissions.